

# HV 8000 - MECHANICAL BOOSTER PUMP

[edwardsvacuum.com](http://edwardsvacuum.com)

HV8000 feature a rugged design for robust and reliable operation in very large scale processes both in the industrial and chemical markets.



## Performance

Stable process for consistent output - Suitable for continuous operation over wide pressure ranges.



## Adaptability

Easy integration and safe - Optional water cooled exhaust gas after cooler, shaft seal safety purge, temperature monitoring and VFD available.



## Reliability

No unplanned downtime - High performance water cooled mechanical shaft seal, large diameter shaft and large helical gears.



## Flexibility

Configured to your needs - Can be supplied with standard motor or without motor to allow a local motor to be fitted. Horizontal or vertical flow to suit application and system design.

## Technical Data

	Units	HV8000
Displacement 50 Hz	m <sup>3</sup> h <sup>-1</sup> /CFM	7200/4241
Displacement 60 Hz	m <sup>3</sup> h <sup>-1</sup> /CFM	8640/5089
Inlet/outlet connection		10" class 150 ASME B16.5
Inlet/outlet cooling water connection		Rp 1/2 ISO 7-1 (1/2 BSP)
End cover purge gas inlet		Rp 3/8 ISO 7-1 (3/8 BSP)
Pressure differential across pump 50 Hz	mbar/torr	190/143
Pressure differential across pump 60 Hz	mbar/torr	120/90
Max cooling water supply pressure	bar/psi	4.0/58
Max cooling water supply temp	°C/F	35/95
Cooling water flow rate	lmin <sup>-1</sup> /US gal min <sup>-1</sup>	15/3.96
Noise level	dB(A)	82
Weight (without motor)	kg/lb	580/1279
Weight (with standard motor) kg	kg/lb	720/1587
Motor Power 50Hz	kW/hp	15/20
Motor Power 60Hz	kW/hp	18.5/25
Oil capacity (vertical gas flow)	litre/gal	8.3/2.18
Dimensions Horizontal flow L x W x H	mm	1737 x 530 x 820
Dimensions Vertical flow L x W x H	mm	1737 x 670 x 638

## Ordering information

Product Description	Part Number
HV8000 VF 400 V 50 Hz 230/460 V 60 Hz 18.5 kW BOOSTER	A311-03-940
HV8000 VF 200 V 50 Hz 200/380 V 60 Hz 18.5 kW BOOSTER	A311-03-934
HV8000 VF BARESHAFT BOOSTER	A311-01-985
HV8000 HF 380/400 V 50 Hz 230/460 V 60 Hz 18.5 kW BOOSTER	A311-04-940
HV8000 HF 200 V 50 Hz 200/380 V 60 Hz 18.5 kW BOOSTER	A311-04-934
HV8000 HF BARESHAFT BOOSTER	A311-02-985

ATEX variants available on request

## Applications

- Steel degassing
- Metallurgy
- Coating
- Process industry

## GLOBAL CONTACTS

Publication Number: 3602 202 9 01  
 © Edwards Limited 2019. All rights reserved.  
 Edwards and the Edwards logo are trademarks of  
 Edwards Limited.

Whilst we make every effort to ensure that we  
 accurately describe our products and services, we give  
 no guarantee as to the accuracy or completeness of any  
 information provided in this datasheet.

Edwards Ltd., registered in England and Wales  
 No. 6124750, registered office: Manor Royal,  
 Crawley, West Sussex RH10 9LW, United Kingdom.

### EMEA

**UK** +44 (0) 1444 253 000  
 (local rate) 0845 921 2223

**Belgium** +32 2 300 0730

**France** +33 1 4121 1256

**Germany** 0800 000 1456

**Italy** +39 02 48 4471

**Israel** +972 8 681 0633

### ASIA PACIFIC

**China** +86 400 111 9618

**India** +91 20 4075 2222

**Japan** +81 47 458 8836

**Korea** +82 31 716 7070

**Singapore** +65 6546 8408

**Taiwan** +886 3758 1000

### AMERICAS

**USA** +1 800 848 9800

**Brazil** +55 11 3952 5000

